

Tunnel Dryer – Power Socket Requirements

Please ensure that the socket is installed, suitably fused and tested prior to dryer installation. We will not hardwire dryers directly into distribution boxes without a socket installed. Please note that dryers are normally shipped with 5 metre cable. The customer will need to arrange for an electrician to connect the dryer.



WPS Essential and Premium requires a 13amp Single Phase Socket (standard UK domestic)
600 (Single Phase - low powered version) requires a 16amp Single Phase Socket – Dryer power rating 15amp

600 (Single Phase – Standard) requires a 32amp Single Phase Socket – Dryer power rating 20amp

700 (Single Phase) – requires a 32amp Single Phase Socket – Dryer power rating 20 – 25amps

700 (Three Phase) – requires a 16amp Three Phase Socket (5 Pin) – Dryer power rating 11amps per Phase

700L (Single Phase) – requires 32amp Single Phase Socket – Dryer power rating 31amps

700L (Three Phase) – requires 16amp Three Phase Socket (5 pin) – Dryer power rating 12 – 16amps per Phase

8220 (Three Phase – only) – requires 32amp Three Phase Socket (5 pin) – Dryer Power rating 20 – 23amps per Phase

8230 (Three Phase – only) – requires 32amp Three Phase Socket (5 pin) – Dryer Power rating 26 – 30amps per Phase



Single Phase – 16amp 3 pin * (Mini low powered version (special order))



Single Phase – 32amp 3 pin * (Mini Standard / 700 Single Phase / 700L Single Phase)



Three Phase – 16amp 5 pin ** (Mini Three Phase / 700 Three Phase/ 700L Three Phase)



Three Phase – 32amp 5 pin ** (8220 / 8230 Three Phase)

- 3 Pin Live / Neutral / Earth ** 5 Pin Phase 1 / Phase 2 / Phase 3 / Neutral / Earth
Please note that dryer power ratings are indicative, SISS retain the right to change specification if required